



LGM-O2/101

CEP ARA ÜTÜ TEZGAHI

POCKET INTERMEDIARY IRONING TABLE




1



2



3





CONNECTIONS

Capacity of ironing per hour(approx.)	-
Steam 5-7,5 bar	-
Condensate max, 0,5 bar	-
Suction min. 120 mbar	-
Compressed air 6 bar	-
Blowing Ø=10 mm	-
Voltage Volt/km	230V / 0,15KW

DIMENSIONS

L x W x H cm (inches)	90x80x125
Weight kg (lbs)	85

CONSUMPTION

Steam kg/H	-
Suction l/min.	-
Compressed air l/min.	-
Blowing l/min.	-

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS

- Ayarlanabilir yükseklik (Boy ayarı)
- Ayrılmış tek ve çiftli ayarlanabilir vakum.
- Merkezi vakum hattına bağlanabilme.
- Buhar ısıtmalı kalıplar.
- Merkezi buharlı el ütüsü.
- Alt üfleme.
- Adjustable height (Height setting)
- Separated single and double adjustable vacuum.
- Ability to connect to the central vacuum line.
- Steam heated molds.
- Central steam hand ironing.
- Blowing feature in the lower mold.